

BW-4 Part Industrial Cable Gland



Size :	20mm to 90mm & ½" to 3½" 3"
Standard :	BS 6121 :Part-1 : 2005 ,EN 50262 :1999
Function :	Provides mechanical cable retention & electrical continuity via armoured wire termination in indoor area.
Ingress Protection:	IP2X EN 60529
Material:	Brass BS 2874
Thread:	Metric & NPT
Operating Temp:	-80°C to +300°C
Cable Type:	SWA Cable
Features:	Universal anyway clamping ring
Accessories:	Shroud ,Earth Tag, Brass Lock Nut and Serrated Washer
Packing:	Gland Kit Contain 1 Brass Cable Gland,1 Brass Lock Nut,1 Brass Earth Tag and 1 PVC Shroud.

Table

Size	Thread "C"		Thread Length "D"	Cable Dia. "A" Max.	Cable Dia. "B" Max.	Armour Wire Dia.	Across Flat	Across Corners	CAT NO.
	Metric	NPT							
20S	20	½"	10	11.70	15.90	0.9-1.25	23.50	26.00	MCBW-420S
20	20	½"	10	14.00	20.00	0.90-1.25	25.00	28.00	MCBW-420
25S	25	¾"	10	18.00	24.00	1.25-1.60	31.00	35.50	MCBW-425S
25	25	¾"	10	20.50	27.00	1.25-1.60	33.00	37.00	MCBW-425
32S	32	1"	10	27.00	33.50	1.60-2.00	40.50	45.50	MCBW-432S
32	32	1"	10	27.00	33.50	1.60-2.00	40.50	45.50	MCBW-432
40S	40	1½"	10	31.50	39.50	1.60-2.00	45.50	50.50	MCBW-440S

40	40	1 1/4"	15	33.50	41.50	1.60-2.00	49.00	55.00	MCBW-440
50S	50	1 1/2"	15	39.50	48.50	2.0-2.50	56.50	63.50	MCBW-450S
50	50	2"	15	44.50	54.50	2.00-2.50	62.50	70.50	MCBW-450
63S	63	2"	15	50.20	59.20	2.50	68.80	77.00	MCBW-463S
63	63	2 1/2"	15	56.50	65.60	2.50	76.00	86.00	MCBW-463
75S	75	2 1/2"	15	63.50	72.00	2.50	86.00	94.50	MCBW-475S
75	75	3"	15	69.50	78.50	250-3.15	90.00	101.00	MCBW-475
90	90	3"	20	80.50	91.00	3.15	100.00	111.50	MCBW-490

Dimensions are in mm