

TRS Cable Gland



Size :	16mm to 50mm
Standard :	BS 6121: Part -1 :2005,EN 50262:1999
Function :	Recommended for use with braided, co-axial or SWA cables. A rubber seal compresses on cable to provide a tight fit against cable.
Ingress:	IP66
Material:	Brass BS 2874
Thread:	Metric
Accessories:	Shroud, Earth Tag, Lock Nut and Serrated Washer
Features:	Outer Displacement Seal
Packing:	Gland Kit for 16mm to 32 mm Contain 2 Brass Cable Gland, 2 Galvanized Steel Lock Nut, 2 Brass Earth Tag and 2 PVC Shroud. For sizes 40 mm and above each kit includes one off each component.

Table

Gland Size	Entry Thread "C" Metric	Length "D"	Cable Dia. "A" Max	Cable Dia. "B" Max.	Across Flat	Across Corners	CAT NO.
16	16	8	3.00	7.00	20.00	23.00	MCTRS-16
20S	20	10	7.00	10.00	24.00	27.00	MCTRS-20S
20	20	10	10.00	14.50	27.70	31.00	MCTRS-20
25	25	10	14.50	20.50	35.00	39.00	MCTRS-25
32	32	10	20.50	26.50	43.00	47.50	MCTRS-32
40	40	15	26.50	34.50	51.50	57.00	MCTRS-40
50	50	15	34.50	43.50	58.50	65.00	MCTRS-50

Dimensions are in mm